



F19L - 6 x 200 mL		
Carbon Fiber Centrifuge Rotor		
RPM	MAX RCF	k factor
19000	55392	702
18000	49715	782
17000	44344	876
16000	39281	989
15000	34524	1126
14000	30074	1292
13000	25931	1499
12000	22095	1759
11000	18566	2093
10000	15344	2533
9000	12429	3127
8000	9820	3958
7000	7519	5169
6000	5524	7036
5000	3836	10132
4000	2455	15831
3000	1381	28145
2000	614	63326
1000	153	253303

422 Aldo Avenue, Santa Clara, CA. 95054-2301  
 800.784.3843 - Fax 408.988.1196  
[www.piramoon.com](http://www.piramoon.com)

- Limited Lifetime Warranty!
- Corrosion free
- Up to 60% lighter than metallic equivalents
- Highly resistant to radiolabel contamination
- Compatible with all popular floor model centrifuges.
- No need for derating after years of use
- Fully autoclavable
- Superior insulating properties, making chilling unnecessary
- Competitively priced at or below the cost of conventional metallic rotors

Offering the rewards of 40 years of aerospace R&D to scientists and researchers everywhere. Not only is carbon fiber at the cutting edge of technology, it is also the most sensible and safe alternative to the standard aluminum and titanium alloys used today for all centrifugation rotors. With properties matching those of steel, but without the negative attributes, carbon fiber is leagues ahead of metal in regards to strength, weight, and malleability. Please contact FIBERLite for further product information.